

RQ-8 Automatic Strapping Machine

- High Speed - up to 40 straps per minute
- Robust, portable design with locking castors
- Easy strap loading
- Ready to operate in less than 25 seconds



Features and Benefits

Self-Correcting Technology

If the RQ-8 is operated without a package on the table, the strap forms a small loop which is ejected from the sealing unit. The machine then re-feeds ready for the next cycle.

Self-Diagnostic Function

Programmable microprocessor constantly monitors critical functions. Any irregularity is immediately displayed.

Variable Tension

A wide range of tension can be selected via a single dial. Tension capability up to 80kg.

Permanently Lubricated Mechanisms

Self-lubricating design reduces wear & tear and increases operational life.

Reliable Motor & Drive Mechanism

Designed with a minimum of moving parts to increase motor life and reduce maintenance.

Energy Saving Auto shut off

Machine enters standby mode after 3 minutes thereby saving energy.

Arch Size	W 650 mm x H 500 mm
Width	1252 mm
Depth	609 mm
Height	1403 mm
Weight	160 kg
Table Height	794 mm
Minimum Package Size	W 80 x H 30 mm
Maximum Package Size	W 620 x H 480 mm
Joint/Strap/Coil	heat seal/polypropylene/ ID 200 x OD 450 x W 200 mm
Strap Width	5, 6, 9, 12, 15.5 mm
Strap Tension	up to 784N (80kgf), 150mm stroke
Speed	1.5 sec./strap, 40 straps per min.
Power Supply	100 – 240V Single phase 50/60Hz 0.65KVA

Dimensions and specifications are subject to change without notice.