

# RQ-8x Automatic Strapping Machine

- High Speed - up to 55 straps/minute
- Robust, portable design with locking castors
- Easy strap loading
- Ready to operate in less than 25 seconds



## Features and Benefits

### Dedicated Tension Motor

Less wear parts (i.e. interlock shaft, tension, pulley) and improved speed.

### Self-Correcting Technology

If the RQ-8x is operated without a package on the table, the strap forms a small loop which is ejected from the sealing unit. The machine then re-feeds ready for the next cycle.

### Self-Diagnostic Function

Programmable microprocessor monitors critical functions and displays any irregularity.

### Variable Tension

A wide range of tension can be selected via a single dial. Tension capability up to 80kg.

### Permanently Lubricated Mechanisms

Self-lubricating design reduces wear & tear and increases operational life.

### Reliable Motor & Drive Mechanism

Designed with a minimum of moving parts to increase motor life and reduce maintenance.

### Energy Saving Auto shut off

Machine enters standby mode after 3 minutes thereby saving energy.

|                      |   |
|----------------------|---|
| Arch Size            | W 650 mm x H 500 mm                                 |
| Width                | 1252 mm   |
| Depth                | 609 mm  |
| Height               | 1403 mm   |
| Weight               | 160 kg  |
| Table Height         | 794 mm  |
| Minimum Package Size | W 80 x H 30 mm                                      |
| Maximum Package Size | W 620 x H 480 mm                                    |
| Joint/Strap/Coil     | heat seal/polypropylene/ ID 200 x OD 450 x W 200 mm |
| Strap Width          | 5, 6, 9, 12, 15.5 mm                                |
| Strap Tension        | up to 784N (80kgf), 150mm stroke                    |
| Speed                | 1.5 sec./strap, 55 straps per min.                  |
| Power Supply         | 100 – 240V Single phase 50/60Hz 0.65KVA             |

*Dimensions and specifications are subject to change without notice.*